

S100

and The second

S100 Skid-Steer Loader

-



One Tough Animal.

Bobcat[®] S100 Skid-Steer Loader Specifications

Performance	S100	
Rated Operating Capacity ¹ Tipping Load Hydraulic Pump Capacity Travel Speed Operating Weight	1000 lb. (453 kg) 2039 lb. (925 kg) 13.1 gpm (49,6 L/min.) 6.5 mph (10,4 km/hr.) 4110 lb. (1864 kg)	
Dimensions		
Length (with bucket) Width (with bucket) Height Height to Bucket Pin	110.2 in. (2800 mm) 50 in. (1270 mm) 73.9 in. (1878 mm) 103.6 in. (2633 mm)	
Engine		
Model Fuel/Cooling Cylinders HP/Displacement	V1505 Diesel/Liquid 4 35.5/94.4 cu. in. (1498 cc)	
Fuel Tank Capacity	11.9 gal. (45 L)	
Operation		
Steering and Drive	Forward, reverse, travel speed and steering controlled by two hand levers.	
Hydraulics	Raise/lower lift arms and dump/rollback bucket controlled by two foot pedals.	
Transmission	Hydrostatic, four-wheel driv	е.
Standard Features	Adjustable Cushion Seat Automatically Activated Glow Plugs Bobcat Interlock Control System (BICS™) Bob-Tach™ Deluxe Cab Engine/Hydraulic Shutdown Front Auxilliary Hydraulics	Front & Rear Lights Lift Arm Support Meters/Gauges/ Warning Lights Parking Brake Seat Bar Seat Belt Spark Arrestor Muffler 27x8.5-15 Heavy-Duty Tires
Options/Accessories	Attachment Control Kit Backup Alarm Cab Enclosure with Heater Catalytic Purifer Flasher/Strobe Lights Flotation Tire 27x10.5-15 Horn Hydraulic Bucket Positioning ²	Service Safety Training Course Skid-Steer Loader Operator Training Kit Sound Cab (Reduces noise at operator's ear) Special Applications Kit ³ Suspension Seat

Lots of Skid-Steer Muscle in a Smaller Package!

Got to get the work done, but don't have much space to maneuver? Give the Bobcat® S100 skid-steer loader a try!

The S100 delivers 1,000 pounds of lift capacity, yet easily fits through narrow openings. It weighs only 4,110 pounds for easy trailering.

With a travel speed up to 6.5 mph, you'll get your longer-run jobs done faster. And this peppy S100 loader is also better balanced for greater work efficiency.

It features proven safety technology — the Bobcat Interlock Control System (BICS[™]). BICS requires the operator to be seated in the loader with the seat bar in place and the engine running. After the "press to operate loader" button is pushed, the hydraulic lift/tilt functions and traction-drive system can be operated.

Plus, with the S100 you get more than an exceptional skid-steer loader — you get unmatched support from a worldwide network of Bobcat dealers offering industry-leading attachments, accessories and parts availability. Their factory-trained service technicians are equipped to handle all your parts and service requirements, including engine and hydrostatic/hydraulic components. There's also an excellent warranty program.

improve your tight-fit job efficiency!

1,000 LB. Rated Operating Capacity

103.6 IN. Lift Height

35.5 HP Liquid-Cooled Diesel Engine

NOTE - Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat skid-steer loaders may show other than standard equipment. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

¹Operating capacity rated with standard digging bucket according to SAE standard J818 – OPERATING CAPACITY TO EQUAL NO MORE THAN ONE HALF THE TIPPING LOAD. ²Bucket positioning helps operator keep the same tilt of the load during lifting.

³Includes polycarbonate front door, top and rear windows

A. 27 x 10.50 - 15 Tires - 45.94 in. (1167 mm) B. 27 x 10.50 - 15 Tires - 38.07 in. (967 mm) C. Bucket Width - 50 in. (1270 mm)

See your Bobcat dealer for details.

The Bobcat \$100 — it's the agile, reliable loader that can

Attachments for this model: Angle Broom

Bobcat

Auger Backhoe **Bale Fork** Breaker **Brush Saw Buckets** Digger **Dumping Hopper** Grapple, Industrial Grapple, Root Grapple, Utility (for use Landplane Pallet Fork Scraper Snow Blade Snowblower Snow V-Blade* Soil Conditioner* Sweeper Three-Point Hitch Tiller Utility Fork

130.15 in. (3306 mm) 7 103.64 in. (2632.6 mm 82.04 in. 73.92 ir 89.07 in. 110.2 in.





www.bobcat.com Printed in U.S.A.

Bobcat Company P.O. Box 6000 • West Fargo, ND 58078