

ENGINE POWERED ARTICULATING BOOM LIFTS

AB26J PLUS (AB850J PLUS)

Compliant with CE/EAC standards

PRODUCT HIGHLIGHTS

Leading Platform Height

- 25.65 m (84'2") platform height, higher than most other brands in this range

Leading Horizontal Outreach

- 19.1 m (62'8") maximum horizontal outreach, longer than most other brands in this range

Increased Platform Capacity

- Update the platform capacity from 230kg to 230kg/340 kg(unrestricted/restricted)

Active Oscillating Axle Function

- allow active oscillating axle function at both stowed and raised positions

4WS With 3 Steering Modes

- Convenience for driving on the narrow job site

Transport in Container

- The new boom structure design allows driving into containers for transportation

Safer Boom Movement Interlock

- The telescopic and lifting of the secondary boom are hydraulic and electric dual interlocked



Standard Features

Hydraulic platform leveling	180°platform rotation	Active oscillating axle function
Proportional control with 3 joysticks	Four-wheel brake	Max allowable tilt angle at 5°
Flashing beacon	Weighing system	4WD x 4WS
Tilt protection system	Emergency lowering system	Fault diagnosis system
Emergency stop system	Horn and buzzer	Motion alarm
Mechanical release for travel braking	7-in smart screen	Tool tray
Manual storage box	Foot switch	360° continuous turntable rotation
Non-marking Foam-filled tires	2.44 m(8') platform with swing gate	
Telematics-ready connector	Secondary guarding device	
AC power to platform		

Options & Accessories

Oil cooler	Solid tires	2nd platform rail for hand protection
Half-mesh	Glazier kit	Platform work light

SINOBOOM™

PARTNERS IN ACCESS™

INFO@SINOBOOM.EU | WWW.SINOBOOM.EU

SINOBOOM B.V., NIKKELSTRAAT 26, 2984 AM RIDDERKERK, THE NETHERLANDS, +31 180 225 666

ENGINE POWERED ARTICULATING BOOM LIFTS
AB26J PLUS (AB850J PLUS)

Compliant with CE/EAC standards

Model	AB26J Plus (AB850J Plus)
Dimensions	
Max Platform Height	25.65 m (84'2")
Max Working Height	27.65 m (90'9")
Max Horizontal Outreach (230kg/340kg)	19.1 m /17.0 m (62'8"/55'9")
Max Up and Over Clearance	9.07 m (29'9")
A Stowed Length	12.09 m (39'8")
B Machine Width	2.49 m (8'2")
C Stowed Height	2.93 m (9'7")
Stowed Length (Transport)	9.49 m (31'2")
Stowed Height (Transport)	3.28 m (10'9")
D Wheelbase	3.0 m (9'10")
Ground Clearance	0.46 m (1'6")
Platform Size (L×W×H)	2.44 m x 0.91 m x 1.1 m (8' x 3' x 3'7")
Performance	
Max Platform Capacity (Unrestricted/Restricted)	230 kg/340 kg (507 lbs/749 lbs)
Max Platform Occupants	2 Persons
Drive Speed (Stowed)	0 ~ 4.8 km/h (0 ~ 3.0 mph)
Drive Speed (Raised)	0 ~ 1.1 km/h (0 ~ 0.7 mph)
Gradeability	45%
Turntable Rotation	360° /Continuous
Platform Rotation	180°
Tilt Rating	5°
Turning Radius (Inside/Outside)	3.65 m/6.91 m (11'12"/22'8") (Two-wheel steering) 2.25 m/4.60 m (7'5"/15'1") (Four-wheel steering)
Turntable Tail-swing	1.13 m (3'8")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	385/65-22.5 /foam-filled
Power	
Drive × Steer	4 WD × 4 WS (2 WS optional)
Engine	43 kW/2500 rpm/QSF2.8T3NA60 / Cummins /China T3/EU Stage 3A 36.5 kW/2200 rpm/YCF3050 / Yuchai /China T3
Hydraulic Tank Capacity	180 L (39.6 gal (UK)/47.6 gal (US))
Diesel Tank Capacity	150 L (33.0 gal (UK)/39.6 gal (US))
System Voltage	12 V DC
Weight	
Weight	18,640 kg (41,094 lbs) (Two-wheel steering) 18,760 kg (41,358 lbs) (Four-wheel steering)
Standards Compliance	
CE/EAC	

